

## **Tank safety shower 821750**

GIA Premix Tank Shower for outdoor use has a volume of 1375 liter with a flow rate up to 76 liter/min. The Tank Shower is suitable where no water lines are available, the water supply is unreliable or if there is a risk of freezing and temperature-controlled water is required.

The water temperature appropriate for emergency use is maintained by a thermostat controlled 3 Kw water heater.

Additives mixed into the water eliminates the risk of bacteria growth and allows you to replace the water only in every 6 months.

The basic design in stainless steel consists of a frame work with a tank on top, insulated on all sides and covered by steel panels.

## Technical data

Art no: 821750

Frame and tank: Stainless steel 1.4301

Insulation: Polystyrene

Shower head: Acetal plastic

Flow rate: Up to 76 lit/min

Tank volume: 1 375 liter

DN25/ G 1" (female), with overfill pro-

tection.

Output: 3 kW, with electronic control

Supply voltage: 400Vac, 3ph, 10A Dimension (L/W/H): 146 x 346 x 160 cm

Accessories

8223563-TANK Eyewash

821510-TANK Alarm with sound and flash

821380 Side panels (3 sides)

821751 PVC curtains at entrance

820398 Platform actuator for emergency



GIA Premix AB www.giapremix.se info@giapremix.se +46 240 59 40 00

